

An investigation into blood clot removal in human vessels using the GP Mechanical Thrombectomy Device (GPMTD)

J Patrick¹, KMC Abrew², YL Hock³, G Selzer⁴, G Pearce⁵, S Dicken⁶, D Cvijan⁷,
A Khan⁸, K Hadley⁹, J Wong¹⁰, G Romero¹¹

¹ Retired Consultant ORLAU, RJA, Oswestry, UNITED KINGDOM

^{2,8} Surgeon, Dept. of Vascular Surgery, Moat Road, Walsall Hospitals NHS Trust, UNITED KINGDOM

^{3,6,7,9} Dept. of Histopathology, Moat Road, Walsall Hospitals NHS Trust, UNITED KINGDOM

⁴ Surgeon Dept. of Orthopaedic Surgery, Moat Road, Walsall NHS Trust, UNITED KINGDOM

⁵ Honorary Research Fellow, Institute of Science Technology and Medicine, Keele University, UNITED KINGDOM

¹⁰ Head of Department of Vascular Surgery, University Hospital, SINGAPORE

¹¹ Graphic Engineering and Simulation Group, Universidad Politécnica de Madrid, SPAIN

gpearce2011@gmail.com

ABSTRACT:

Blood clots may occur in vessels like arteries and veins, being the strokes one of the commonest cause of death and severe disability; deep vein Thrombosis is also a common problem. In this pilot study we investigate the effect of removing a blood clot in a dissected human vein with a novel thrombectomy device. Following successful simulations of the device, we show using histological staining techniques, that the removal of a clot by this novel device, does not cause any apparent damage to the vessel wall, when suction pressures of up to 85kPa are applied. We conclude that this device may potentially be very useful as a blood clot removal device in human vessels.

Keywords: Blood clot removal, Histopathology, Thrombectomy, Arteries, Veins, Deep Vein Thrombosis, Stroke

INTRODUCTION

Blood clots may occur in vessels e.g. arteries and veins (giving rise to Strokes and Deep Vein Thrombosis). Stroke is the third commonest cause of death in the UK with 53,000 deaths in 2007 [1] and can cause severe disability, with 40% of cases left with severe impairment [2]. Deep vein Thrombosis (DVT), is also a common problem. The exact number of people affected by DVT/PE is not known, however estimates range from 300,000 to 600,000 (1 to 2 per 1,000, and in those over 80 years of age, as high as 1 in 100) per annum in the United States. Estimates also suggest that 60,000-100,000 Americans die of DVT/PE [3].

Treatments for DVT include anti-coagulants such as warfarin and interventional methods such as percutaneous mechanical thrombectomy devices e.g. the Amplatz; Bacchus Fino device; the Arrow-Trerotola percutaneous thrombolytic device [4]. Although acute thrombolytic treatment has been shown to be a highly effective interventional method, it can be associated with a risk of bleeding and is contraindicated in pregnancy, after trauma, or postoperatively [5]. Mechanical Thrombectomy Devices (MTDs) have increased in use and have been shown to restore blood flow in patients suffering from thromboembolic stroke [6]. Such devices include e.g. the MERCI (Mechanical Embolus Removal in Cerebral Ischemia) [7], the penumbra device [8].

Other examples include rheolytic catheters (Angiojet) [9]. However, devices may carry a potential risk of breakage of moving parts, some potential risk of penetration of the vessel wall, and downstream embolisation due to fragmentation of the clot. Another thrombo-mechanical extraction device being developed is called the GPTAD (GP Thrombus Aspiration Device). A schematic view of the GP MTD, is shown in figure 1 [10-11]. The device may potentially reduce the risk of downstream embolization (since it does not have to touch the clot or insert into the clot to facilitate clot removal). It also has no moving parts (thereby potentially reducing the risk of breakage), and in-vitro studies [12] have shown that it potentially reduces the risk of clot fragmentation compared to using a straight tube without any helical configuration.




Fig.1 The GPTAD

The device has been mathematically designed and optimised, using techniques including Bond Graph

modelling, and CFD modelling [13]. Figure 2 below shows an example of the type of modelling undertaken with CFD and shows the distribution of forces (typical pressures used) in the GPTAD itself during clot removal simulation of a blood clot of diameter about 3mm occluding a vessel [14].




Fig.2 CFD Simulation of the GPTAD. (Romero et al 2014).
Reproduced with kind permission: UKSIM Proceedings, ISBN 978-1-4799-4923-6, pp100-104.

METHODS AND MATERIALS

The study was undertaken with ethical approval having been granted by the NHS LREC (LREC reference number 07Q2702/23). Materials: GP Mechanical Thombectomy Device with an internal diameter of 1 mm at the tip (GP MTD, Dresden, Germany) (figure 1); a suction pump with a pressure range of 0-100 kPa (Welch model number 2622C-02, Gardner Denver, Sheboygan, Wisconsin, USA); Vacuum flask. The apparatus used is shown in figure 3.




Fig. 3 The Apparatus used in the Experiments

A freshly dissected popliteal vein (the amputated limb had been removed a few minutes before) was used and the 1mm internal diameter GPTAD was passed along the 4 mm wide vein. The tip of the GPTAD was positioned 3mm proximally from a clot. Pathological sections of the vein wall were taken (i) at the point where suction of the clot had been undertaken at 18mm from the open end of the vein and (ii) at points of direct suction onto the vein wall (middle part of vein) (sucking for 30seconds at a pressure of 85kPa), and (iii) at a distal point on the vein wall where no suction had taken place. The latter served as a control.

Previous sections were processed (as routine histological material embedded in paraffin blocks and 5 micron sections were cut and embedded on the glass slides for histological examination). The sections were examined for any damage (caused by suction with the GPTAD) using Elastic Van Gieson staining, and Immunoperoxidase staining for type IV collagen. Technique for Collagen IV. (Benchmark XTT IHC/ISH staining module courtesy of the Department of Histopathology, Manor Hospital, Moat Road, Walsall WS2 9PS). The Van Gieson stain may be found in document number SOP Number SS 28 pages 1 to 6 edition number 3.0, Walsall Hospital NHS Trust.

RESULTS

Following figures presents different results after the use of the GPTAD with different conditions. In these figures, a 250 zoom factor has been used and the 'A' note indicates the site of the applied suction.




Fig.3 Section of vein at the site of clot removal by the GPTAD (Elastic Van Gieson stain).



Fig.4 Section of vein at the site of clot removal by the GPTAD. (Immunoperoxidase staining for type IV collagen).



Fig.5 Section of the middle part of the vein. (Immunoperoxidase staining for Type IV collagen).



Fig.6 Section of normal (the control) vein; no suction applied (Elastic Von Gieson stain).



Fig.7 Section of normal (the control) vein; no suction applied. (Immunoperoxidase staining for type IV collagen).



Fig.8 Section of middle part of vein. (Elastic Van Gieson stain).

DISCUSSION

Histological analysis of the sections taken from the vein wall indicated that there was no apparent intimal, medial or adventitial damage either on routine histological morphology or on special stains with Van Giesen and PAS staining. Type IV collagen immune-stains did not show any significant abnormality on the popliteal vein specimen. Although this is a pilot study (which will be extended) for this new device, we believe that the results indicate that the GPTAD could potentially be a useful device to use in blood clot removal in vessels.

CONCLUSIONS

From our study we conclude that the results are consistent with previous mathematical modelling indicating that the forces needed to extract a blood clot from a vessel wall are within the range used to extract a blood clot from the vein. This indicates that the GPTAD may therefore have potential use in the removal of blood clots in human vessels.

In addition, the Van Gieson stain, the PAS and immuno-stains all indicated that there was no histological damage apparent in the vein wall at the site of clot removal by the GPTAD, or at sites where direct sucking using pressures of 85kPa was applied.

ACKNOWLEDGEMENT

We thank the Histopathology Department Walsall Hospital NHS Trust for the use of facilities to undertake this study. We thank the patient who donated their amputated lower limb for use in the study, in accordance with LREC reference number 07Q2702/23.

REFERENCES

- [1] Scarborough P, Peto V, Bhatnagar P, Kaur A, Leal J, Luengo-Fernandez R, Gray A, Rayner M and Allender S (2009) British Heart Foundation and Stroke Association, British Heart Foundation Health Promotion Research Group and Health Economics Research Centre, Department of Public Health Stroke Statistics.
- [2] National Collaborating Centre for Chronic Conditions. (2008) Stroke: national clinical guideline for diagnosis and initial management of acute stroke and transient ischaemic attack (TIA). London: Royal College of Physicians. National Institute for Health and Clinical Excellence: Guidance.
- [3] Centers for Disease Control and Prevention website. <<http://www.cdc.gov/ncbddd/dvt/data.html>>
- [4] Augustinos, P., and ; Ouriel, K., (2004) Invasive approaches to Treatment of Venous Thromboembolism. *Circulation*, 110 (9 Suppl 1): 127-134.
- [5] Alteplase for the treatment of acute ischaemic stroke guidance [TA122] (2007). Replaced by TA264 Stroke (acute, ischaemic) – alteplase (2012).
- [6] Davis S, Lees K, Donnan G. (2006) Treating the acute stroke patient as an emergency: current practices and future opportunities. *International Journal of Clinical Practice*, 60(4):399-407
- [7] Gobin YP, Starkman S, Duckwiler GR, Grobelny T, Kidwell CS, Jahan R, Pile-Spellman J, Segal A, Vinuela F, Saver JL. (2004) MERCI 1: a phase 1 study of Mechanical Embolus Removal in Cerebral Ischemia. *Stroke*, 35:2848-54
- [8] Bose H, Henkes K, Alfke W, Reith. TE, Mayer A, Berlis V, Branca SP. (2008) The Penumbra System: A Mechanical Device for the Treatment of Acute Stroke due to Thromboembolism. *American Journal of Neuroradiology*, 29:409
- [9] Bellon RJ, Putman CM, Budzik RF, Pergolizzi RS, Reinking GF, Norbash AM. (2001) Rheolytic thrombectomy of the occluded internal carotid artery in the setting of acute ischemic stroke. *American Journal of Neuroradiology*, 22:526-30
- [10] Pearce G, and Perkinson ND, "Biomechanical Probe". (2006) International Patent Corporate Treatise (WO2006120464) published 2006-11-16; European patent (EP1893195 (A2)) published 2008-03-05; Japanese patent (JP2008639924 (T)) Published 2008-11-20; Chinese patent (CN101208049 (A)) published 2008-06-25
- [11] Pearce, G., Perkinson, N.D., Wong, J., Burley, M., Spence, J., Brookfield, P. and Murcott, D. 'The 'GP' Mechanical Thrombectomy Device' (2009). *Journal of Stroke and Cerebrovascular Diseases*, 18(4) 288-293.
- [12] Tennuci C, Pearce G, Wong J, Nayak S, Jones T, Roffe C. (2011) Comparison of the effectiveness of three methods of recanalization in a model of the middle cerebral artery: Thrombus aspiration via a 4F Catheter, thrombus aspiration via the GP Thromboaspiration Device and mechanical thrombectomy using the SolitaireTM thrombectomy device. *Stroke Research and Treatment*, Article ID 186424.

- [13] Romero, G., Pearce, G., (2010) Modelling and simulation of a Thrombectomy Probe applied to the Middle Cerebral Artery by using the Bond Graph technique. 9th International Conference on Bond Graph Modeling and Simulation - ICBGM 172-179. Orlando (United States)
- [14] Romero, G., Pearce, G., Wong, J., (2014) Analysis of the GPATD: geometrical influence on blood clot extraction using CFD simulation, UKSIM ISBN 978-1-4799-4923-6, 100-104